



---

## MERCHANT FLUSH BULKHEAD INSTALLATION GUIDE

**Product codes:** 09781, 09782, 09783

---

Class I, 230V~/50Hz. Max 25W. Takes 1x G9 lamp (not included).  
IP64 - for outdoor use.

### **Electrical Safety Warning**

- Always disconnect the main power before starting any electrical work.
- Ensure the installation site is isolated and safe.
- All work must comply with IET Wiring Regulations (BS7671).
- If the product is not double insulated, it **must be earthed**.
- Electrical installations should be carried out by a **Competent Person** or someone with relevant experience, and in accordance with the appropriate Competent Person Scheme.
- The circuit must be protected by a **Residual Current Device (RCD)** that is functioning correctly and has been tested by a qualified electrician.
- Before installing the lighting unit, consult safety guidance from the **Health and Safety Executive**.

### **Installation Instructions**

**IMPORTANT:** If you are unsure at any point, **STOP** and seek professional assistance. Do not proceed unless you are confident.

1. Use a screwdriver to remove the screws connecting the lamp cover (net) to the base.
2. Open the base to access the internal wiring and locate the rubber grommets.

Address: Navigator Lighting (part of Lampfix) Unit 6 Fen End, Stotfold, Hitchin, Herts. SG5 4BA

Tel: 01462 731173 | Email: [sales@navigatorlighting.co.uk](mailto:sales@navigatorlighting.co.uk) | Website: [navigatorlighting.co.uk](http://navigatorlighting.co.uk)

V1 28.10.2025



# Navigator

3. After marking and drilling your chosen spot, carefully insert the wall plugs.
  4. Mount the base to the ceiling, securing it with the plugs, rubber grommets, and screws.
  5. Ensure the rubber is centered and that the hole is slightly smaller than the rubber for a snug fit.
  6. Attach the lamp to the base.
  7. Align the rubber between the base and the lamp cover before securing it.
  8. Double-check that the rubber remains properly centered.
  9. Confirm the glass and rubber are securely installed. Tighten the screws gently—first to the right, then to the left—to ensure the rubber is evenly compressed.
- 

Address: Navigator Lighting (part of Lampfix) Unit 6 Fen End, Stotfold, Hitchin, Herts. SG5 4BA

Tel: 01462 731173 | Email: [sales@navigatorlighting.co.uk](mailto:sales@navigatorlighting.co.uk) | Website: [navigatorlighting.co.uk](http://navigatorlighting.co.uk)

V1 28.10.2025