



PHAROS COMPACT UP & DOWN WALL LIGHT INSTALLATION GUIDE

Product codes: 09785, 09786, 09787

Class I, 230V~/50Hz. 2x GU10, max 6W light bulb (not included).
IP44.

WARNING: Never take risks with electrical safety. Always disconnect the main power before beginning any electrical work and test that it is isolated. It is NOT enough just to turn off the light switch. Electrical products must be installed in accordance with IET regulations (BS7671). If you are in any doubt, always consult a qualified electrician or an experienced person registered with an electrical Competent Person Scheme. Further information is available online or from your Local Authority. If the lighting circuit is not protected by a Residual Current Device (RCD) then the installation should be carried out and tested by a qualified electrician. If necessary, use a suitable stepladder but first read the safe use advice given by the Health and Safety Executive.

In addition to the contents of this kit, you will need:

- 2 Lamps Led GU10 6W max.
- 3-core power cable with earth.
- Appropriate tools and fixings.

IMPORTANT: If you are in any doubt, STOP and seek professional help. Do not proceed unless you are sure.

- Unscrew the two screws with a screwdriver on the right and left of the lamp.
- Open the lid slowly. Unscrew the ground wire from the terminal and place the body of the lamp in a safe place to prevent it from falling and breaking the glasses.
- Place the base of the lamp at the point of the wall where you want to place it and

Address: Navigator Lighting (part of Lampfix) Unit 6 Fen End, Stotfold, Hitchin, Herts. SG5 4BA

Tel: 01462 731173 | Email: sales@navigatorlighting.co.uk | Website: navigatorlighting.co.uk

V1 28.10.2025



mark the two large holes with a pencil.

- If the installation is done on a cement wall you will need a 6 mm drill and a hand drill.
- Place the wall plugs, pass the cable through the rubber terminal by drilling it and tighten the lamp base evenly to the wall.
- Place wire in the terminal following the markings.
Earth in the middle, blue wire in N and brown wire in L.
- Place the lamps.
- Take the body of the lamp, screw the earth wire to the opposite side from where you placed the earth on the terminal.
- Check that the rubber is in place and close the lamp cover by screwing evenly the two screws on the right and left.

The manufacturer bears no responsibility for any injury or damage resulting from incorrect installation or use of the product.

Address: Navigator Lighting (part of Lampfix) Unit 6 Fen End, Stotfold, Hitchin, Herts. SG5 4BA

Tel: 01462 731173 | Email: sales@navigatorlighting.co.uk | Website: navigatorlighting.co.uk

V1 28.10.2025